

Effects of heterogeneities on the hydromechanical behaviour of bentonite-based engineered barriers: Results and current works at Laboratoire Navier

Authors:

Darde B.^{1,2}, Tang A. M.¹, Talandier J.², Dangla P.¹, Pereira J.-M.¹, Roux J.-N.¹, Vu M. N.²

1: Université Paris-Est, Laboratoire Navier, UMR 8205 (ENPC – IFSTTAR – CNRS), France

2: Andra R&D, Châtenay-Malabry, France

Contents

I - Context

II - Control of suction

III - Swelling pressure of bentonite-based materials

IV - Pellets-powder mixtures

V - Current works

Contents

I - Context

II - Control of suction

III - Swelling pressure of bentonite-based materials

IV - Pellets-powder mixtures

V - Current works

I – Context

Radioactive waste disposal:

French concept (ANDRA):


Compacted bentonite-based materials used as engineered barrier (swelling potential, retention capacity, low permeability)

Saturation from the host rock pore water:


Swelling pressure develops against host rock

Study of hydromechanical behaviour upon hydration (suction decrease) at laboratory scale:

Hydration tests



French radioactive waste disposal concept. In red: sealing plugs made of bentonite-based materials (ANDRA).



Swelling of bentonite-based engineered barrier upon hydration

Contents

I - Context

II - Control of suction

III - Swelling pressure of bentonite-based materials

IV - Pellets-powder mixtures

V - Current works


II – Control of suction

Hydration at laboratory scale:

Hydration: vapour phase

Controlling suction allows the material behaviour to be studied during hydration transient stages


Highly compacted bentonite: Saturated at high suction values in constant volume conditions



Water retention curves of three soil samples.

II – Control of suction

Vapour equilibrium technique:



- 1 – Soil sample
- 2 – Desiccator
- 3 – Glass cup
- 4 – Support
- 5 – Over saturated salt solution



Soil sample in a dessiccator

Salt	Relative humidity (%)
$\text{Mg}(\text{NO}_3)_2$	55
NH_4NO_3	65
NaNO_2	66
NaNO_3	75
NaCl	76
Na_2CO_3	91
KNO_3	93
K_2SO_4	97

Relative humidity imposed by some salts at $T = 20^\circ\text{C}$.
After Delage et al., 1998.

Imposing suction by imposing relative humidity in a dessiccator
(Tang, 2005)

II – Control of suction

Kelvin's law:

$$s = \frac{RT}{Mg} \ln(RH)$$



Relates the relative humidity to suction, at constant temperature


- s: suction;
- R: constant of perfect gases;
- T: absolute temperature;
- M: molar mass of water;
- g: gravity acceleration;
- RH: relative humidity

Salt	Relative humidity (%)	Suction (MPa)
Mg(NO ₃) ₂	55	82
NH ₄ NO ₃	65	59
NaNO ₂	66	57
NaNO ₃	75	40
NaCl	76	38
Na ₂ CO ₃	91	13
KNO ₃	93	9
K ₂ SO ₄	97	4

II – Control of suction


Examples of application :

Constant-volume cell:



Wang, 2012

Suction-controlled oedometer:



Wang, 2012


II – Control of suction

Examples of application :

Hydromechanical behaviour of soils:


Mechanical loading at constant suction

Wetting/Drying at constant load



Barcelona Basic Model (after Alonso et al. 1990)

Suction-controlled oedometer:




Wang, 2012

II – Control of suction

Examples of application :

Constant-volume cell:



Hydration: Swelling prevented



Axial pressure sensor: Swelling pressure measurement

Wang, 2012

II – Control of suction

Examples of application :

Vapour equilibrium technique: Suction control



Contents

I - Context

II - Control of suction

III - Swelling pressure of bentonite-based materials


IV - Pellets-powder mixtures

V - Current works

III – Swelling pressure of bentonite

Swelling pressure :

Same relationship for pure bentonite, sand/bentonite mixtures; claystone/bentonite mixtures



$$\rho_{db} = \frac{B \rho_m G_{si} \rho_w}{G_{si} \rho_w (1 + w_m) - \rho_m (1 - B)}$$

ρ_{db} : final dry density of bentonite

B: bentonite content in dry mass

ρ_m : unit mass of the mixture

G_{si} : specific gravity of material i (sand, claystone...)

w_m : water content of the mixture


ρ_w : water unit mass

Relationship between swelling pressure and bentonite final dry density (Wang, 2012)

III – Swelling pressure of bentonite

Swelling pressure :

Relationship between swelling pressure and final bentonite dry density



$$\sigma_s = \alpha \exp(\beta \rho_{db})$$


Bentonite	α	β	Montmorillonite Content (%)	Type
MX 80	1.78×10^{-4}	6.75	75–90	Na
FEBEX	9.80×10^{-5}	6.85	92	Ca
FoCa	7.83×10^{-7}	9.24	50 Beidellite 50 Kaollite	Ca
Kunigel V1	3.67×10^{-3}	3.32	48	Na

Relationship between swelling pressure and bentonite final dry density (Wang, 2012)

III – Swelling pressure of bentonite

Heterogeneities:

Constant volume conditions: Swelling pressure develops upon suction decrease




Swelling pressure test (Wang, 2012)

III – Swelling pressure of bentonite

Heterogeneities :


Technological voids : Swelling does not occur in true constant-volume conditions

Dry density reduction: Influences the swelling pressure



Laboratory study:

Sample first allowed to swell freely, then constant volume conditions are applied and the swelling pressure is measured




Relationship between swelling pressure and swelling strain allowed before constant-volume conditions. Initial dry density is 1.90 Mg/m³ (Wang, 2012)

III – Swelling pressure of bentonite

Heterogeneities :

Technological voids : Heterogeneous density

Preferential flow pathways suspected



Relationship between hydraulic conductivity and final void ratio (Wang, 2012)

Contents

I - Context

II - Control of suction

III - Swelling pressure of bentonite-based materials

IV - Pellets-powder mixtures

V - Current works

IV – Pellets-powder mixtures

Candidate material for engineered barriers:

Reduction of technological voids

Compaction easier


Operational convenience




MX80-bentonite pellets-powder mixture

Upon hydration:

Homogenisation of the mixture



Evolution of a granular bentonite sample during hydration (Hoffmann et al. 2007)



Density variation upon hydration of a bentonite pellets-powder mixture. (van Geet et al. 2005)


IV – Pellets-powder mixtures

Heterogeneities:

Heterogeneous distribution of pellets and powder in the samples (initial state)

Local rearrangements of the granular assembly during swelling

Hydro-mechanical behaviour of the mixture?



X-ray computed microtomography images of a mixture of bentonite pellets-powder mixture.

(a) One layer of pellets; powder

(b) Two layers of pellets; powder

(c) Pellets and powder previously mixed

(Molinero-Guerra et al. 2017)

Contents

I - Context

II - Control of suction

II - Swelling pressure of bentonite-based materials

IV - Pellets-powder mixtures

V - Current works

V – Current works

Hydro-mechanical behaviour of bentonite pellets-powder mixture:

Swelling pressure tests:

- *Constant volume cells, suction controlled by vapour equilibrium technique,*
- *Influence of powder content,*
- *Test duration: >1 year*

DEM simulations:

- *Model hydration at high suction values (granular assembly) in the constant volume cell,*
- *Influence of local heterogeneities on swelling pressure at high suction values,*
- *Comparison with experimental results*

V – Current works

Experimental device:



Pellets: sub-spherical, diameter 7 mm

Cell height: 30 mm; ~4 pellets layers

Cell diameter: 60 mm

Test duration: >1 year

Pressure sensor: measure swelling pressure upon suction decrease



V – Current works



Discrete Element Method:

Pellets: beads in the simulations


Swelling: impose a radius increase in the simulations

Hydration: reduce modulus in the simulations

Hertz's law: relates normal force to deflection at contact area







$$N_{ij} = \frac{E}{3(1-\nu^2)} (2R)^{1/2} h_{ij}^{3/2}$$



➔ Determine swelling behaviour and modulus decrease upon suction decrease

V – Current works



Thank you for your attention

Presenting author:

Benjamin Darde (PhD student)

Andra

Ecole des Ponts ParisTech

email: benjamin.darde@enpc.fr

References

- Alonso, E.E.; Gens, A.; Josa, A. 1990. A constitutive model for partially saturated soils. *Géotechnique*. 40 (3). 405-430.
- Delage, P.; Howat, M.D.; Cui, Y.-J. 1998. The relationship between suction and swelling properties in a heavily compacted unsaturated clay. *Engineering Geology*. 50. 31-48.
- Dixon, D.A., Gray, M.N., Graham, J. 1996. Swelling and hydraulic properties of bentonites from Japan, Canada and USA. In *Proceedings of the second International Congress on Environmental Geotechnics*, Osaka, Japan, pp. 5–8.
- Feia, S.; Gjabezloo, S.; Bruchon, J.-F.; Sulem, J.; Canou, J; Dupla, J.-C. 2014. Experimental evaluation of the pore-access size distribution of sands. *Geotechnical Testing Journal*. 37 (4).
- Gatabin, C.; Touze, G.; Imbert, C.; Guillot, W.; Billaud, P. 2008. ESDRED Project, Module 1-Selection and THM characterization of the buffer material. In *International conference underground disposal unit design&emplacement processes for a deep geological repository*, 16-18 June, Prague.
- Hoffmann, C.; Alonso, E.E.; Romero, E. 2007. Hydro-mechanical behaviour of bentonite pellet mixtures. *Physics and Chemistry of the Earth*. 32. 832-849.
- Imbert, C.; Villar, M.V. 2006. Hydro-mechanical response of a bentonite pellets-powder mixture upon infiltration. *Applied Clay Science*. 32 (3–4). 197-209.
- Karnland, O., Nilsson, U., Weber, H., Wersin, P. 2008. Sealing ability of Wyoming bentonite pellets foreseen as buffer material-Laboratory results. *Physics and Chemistry of the Earth*. 33. S472–S475 Parts A/B/C.
- Molinero-Guerra, A; Mokni, N.; Delage, P.; Cui, Y.-J.; Tang, A.M.; Aïmedieu, P.; Bernier, F.; Bornert M. 2017. In-depth characterisation of a mixture composed of powder/pellets MX80 bentonite. *Applied Clay Science*. 135. 538-546.
- Muñoz-Castelblanco, J. 2011. Comportement hydromécanique d'un loess naturel. Thèse de Doctorat de l'Université Paris-Est.
- Tang, A.M. 2005. Effet de la température sur le comportement des barrières de confinement. Thèse de Doctorat de l'Ecole nationale des ponts et chaussées.
- Van Geet, M.; Volckaert, G.; Roels, S. 2005. The use of microfocus X-ray computed tomography in characterising the hydration of a clay pellet/powder mixture. *Applied Clay Science*. 29. 73-87.
- Wang, Q. 2012. Hydro-mechanical behaviour of bentonite-based materials used for high-level radioactive waste disposal. Thèse de Doctorat de l'Université Paris-Est.

Strain model

From BExM model (Alonso et al. 1999)

Microstructural volumetric strain :

$$d\varepsilon_{vm}^e = \frac{dp'}{K_m}$$

$$K_m = \frac{\exp(\alpha_m p')}{\beta_m}$$

Alonso E. E. et al. – Engineering Geology (1999) **54**, 173-183




E (s)




$$\varepsilon_{vm}^e = -\frac{\beta_m}{\alpha_m} [\exp(-\alpha_m p'_0) - \exp(-\alpha_m p')]$$

Modulus model




Crushing tests results :



- Axial direction : model for spherical pellets



- Radial direction: model for cylindrical pellets



Model for spherical pellets :



Model for cylindrical pellets

